



WellBAC Comfort Plus Carpet Tile - US Milliken

Final Assembly: LaGrange, Georgia, USA

Life Expectancy: 15 Year(s)

End of Life Options: Recyclable (100%)

Ingredients:

Calcium Carbonate; Nylon 6,6; Nylon 6; Oxirane, methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1); POLYETHYLENE TEREPHTHALATE/POLYBUTYLENE TEREPHTHALATE; Polypropylene; Asphalt; Polymer; Acetic acid ethenyl ester, polymer with ethene; 4,4'-Methylenediphenyl diisocyanate; Water; Glass Fiber; Hydrocarbons, C6-20, polymers, hydrogenated; Polymethylenepolyphenyl polyisocyanate, glycerol ethoxylated / propoxylated, copolymer; Diethylene Glycol; Amorphous Quartz; Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1); Salt of polycarboxylic acid; Stearic Acid; Caprolactam; Benzene, 1-isocyanato-2-[(4-isocyanatophenyl)methyl]-; Carbon black; Acetic acid ethenyl ester, polymer with ethenol; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Polyethylene; (Z)-N-(2-aminoethyl)-N-(2-hydroxyethyl)-9-octadecenamide; 1,3,5-Triazine-2,4,6(1H,3H,5H)-trione, 1,3,5-tris[[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]-; 13-Docosenamide, N-octadecyl-, (Z)-; 1H-Imidazole-1-ethanol, 2-(heptadecenyl)-4,5-dihydro-; 2-(2-aminoethylamino)ethanol; 2-Propenoic acid, polymer with ethene, zinc salt; Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester; Butanedioic acid, sulfo-, 1,4-bis(2-ethylhexyl) ester, sodium salt; Dodecanedioic Acid; Fatty acids, C16-18; Fatty acids, montan-wax, 1-methyl-1,3-propanediyl esters; Hexanedioic acid, polymer with hexahydro-2H-azepin-2-one and 1,6-hexanediamine; Melamine; Petroleum resins; Phenol, 2,4-bis(1,1-dimethylethyl)-, phosphite (3:1); Phosphorous trichloride, reaction products with 1,1'-biphenyl and 2,4-bis(1,1-methylethyl)phenol; Sorbitan, tri-9-octadecenoate, poly(oxy-1,2-ethanediyl) derivs., (Z,Z,Z)-; Zinc Stearate; Titanium dioxide; Anthra[2,1,9-def:6,5,10-d'e'f'] diisoquinoline-1,3,8,10(2H,9H)-tetrone, 2,9-bis(3,5-dimethylphenyl)-; C. I. Pigment Blue 15; C.I. Pigment Brown 24; C.I. Pigment Green 7; C.I. Pigment Yellow 119; Iron oxide; Iron Oxide; Nickel, 5,5'-azobis-2,4,6(1H,3H,5H)-pyrimidinetrione complexes; Benzene, C10-13-alkyl derivs.; N,N'-bis(2,2,6,6-tetramethyl-4-piperidyl)isophthalamide; Siloxanes and Silicones, di-Me, hydroxy-terminated, ethoxylated propoxylated; Amylopectin, 2-hydroxy-3-(trimethylammonio)propyl ether, chloride; Potassium bromide (KBr); Phosphinic acid, phenyl-; Sulfuric acid, mono-C10-16-alkyl esters, ammonium salts; Benzene, 1,1'-methylenebis[2-isocyanato-; Butene, polymer with ethene; Poly(oxy-1,2-ethanediyl), alpha-phosphono-omega-(dodecyloxy)-, compd. with 2,2'-iminobis[ethanol], (EO 2-8 mol)

Living Building Challenge Criteria: Compliant

I-13 Red List:

- LBC Red List Free % Disclosed: 100% at 100ppm
- LBC Red List Approved VOC Content: Not Applicable
- Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

MKN-0026
EXP. 01 NOV 2024
Original Issue Date: 2018

