

OBEX™ TILE: LOOP

SPECIFICATION SHEET DATE: 18 JUNE 2021

MODULAR TILE

Construction

Tufted, Multi-Level Loop

Tile Size

50 cm x 50 cm

Textile Yarn Type

ECONYL® Solution-Dyed Nylon Type 6 and Solution-Dyed Nylon Monofilament

Dye Method

Solution Dye

Tufted Face Weight

946 g/m²

Gauge

1/12

Stitches Per Inch

11.13

Tufts

2,100/100 cm²

Finished Pile Height

6.48 mm

Average Density

5,739

Nominal Total Thickness

9.91 mm

Nominal Total Weight

3,540 g/m²

Standard Backing

PVC-Free WellBAC™ Comfort Cushion (Available with TractionBack™)

Recycled Content by Total Weight

33.3% Pre-Consumer
6.6% Post-Consumer

Flammability (Radiant Panel)

CHF: 4.0 kW/ m²
Smoke Value: 467 %.min

Smoke Density (NFPA-258 or ASTM-E-662-15a)

≤ 450

Methenamine Pill Test (CPSC FF 1-70 or ASTM D 2859-96)

Self-Extinguishing

Lightfastness (AATCC 16.3)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 at 80 Hours

Static Electricity (AATCC-134) 20% R.H., 70°F

≤ 3.5 KV, Permanent Conductive Fiber

Recommended Maintenance

Daily Vacuum and Deep Clean with Hot Water Extraction

Indoor Air Quality - CRI Green Label Plus™

GLP7205, Carpet Category 13X

Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

12 Tiles per box (3 m²)

ADA / BS 8300 / ISO 21542 Compliant

Warranties

5 Year Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release

Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)
Lifetime Dimensional Stability

Lifetime Tufted Bind
Lifetime Edge Ravel
Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.