BPIR
Building Product
Information Requirements

MILLIKEN (AUSTRALIA) PTY LTD NON-REACTIVE STANDARD ADHESIVE PRODUCTS

PRODUCT CLASS

Class 1: Batch or mass-produced products.

PRODUCT NAME (S)

Non-Reactive Standard Adhesive.

PRODUCT DESCRIPTION AND ITS INTENDED USE

- Milliken Non-Reactive Standard Adhesive, solvent-free, pressure-sensitive acrylic emulsion adhesive for bonding modular carpet tiles to substrate.

PRODUCT IDENTIFIER

Milliken Non-Reactive Standard Adhesive.

PLACE MANUFACTURED (NEW ZEALAND OR OVERSEAS)

- Milliken (Australia) Ltd, 171 Briens Road, Northmead, NSW 2152, Australia
- Milliken Floorcovering, 924 Milliken Rd, Spartanburg, SC 29303. USA
- Milliken Floorcovering, Beech Hill Plant, Gidlow Lane, Wigan, WN6 8RN, United Kingdom
- Milliken Textile (Zhangjiagang) Co., Ltd. 19 North Guotai Road, Zhangjiagang, Jiangsu, P.R. China, 215638

RELEVANT BUILDING CODE CLAUSES

B2 DURABILITY	• Performance clause B2.3.1 c) 5 years
F2 HAZARDOUS BUILDING MATERIALS	• Performance clause F2.3.1

HOW THE BUILDING PRODUCT IS EXPECTED TO CONTRIBUTE TO COMPLIANCE

B2 DURABILITY - B2.3.1 c) 5 years	• Milliken modular carpet tiles have a durability of beyond 5 years, based on NZBC B2/VM1 clause 1.1 in-service history. • Durability is supported by a limited warranty for the Lifetime of the carpet tile.
F2 HAZARDOUS BUILDING MATERIALS - F2.3.1	• Milliken Non-Reactive Standard Adhesive is manufactured from non-toxic materials.

LIMITATIONS ON THE USE OF THE BUILDING PRODUCT

- Suitable for interior use only.

DESIGN REQUIREMENTS THAT WOULD SUPPORT THE APPROPRIATE USE OF THE BUILDING PRODUCT

- Suitable for installation of modular carpet tiles.

BPIR
Building Product
Information Requirements

MILLIKEN (AUSTRALIA) PTY LTD NON-REACTIVE STANDARD ADHESIVE PRODUCTS

INSTALLATION REQUIREMENTS

- Apply in accordance with Milliken application instructions.
- Using 1/16" x 1/32" U-notch trowel - estimated coverage 4.4 - 5.5 m2/L.
- Using ¾" - 1" nap paint roller - estimated coverage up to 8.5 m2/L.
- Open time indefinite.
- Dry time 10 - 20 minutes.
- Working time indefinite.
- Concrete substrates - apply 60 days minimum after pour (no testing required).
- Existing on-ground concrete substrates require confirmation of presence of below ground vapour barrier in accordance with AS/NZS 2904 or AS 3660.1 and placed in accordance with AS 2870.
- Where vapour barrier is not present or presence is unknown
- Carpet tiles with WellBAC® Comfort and Comfort Plus cushion backing, a Relative Humidity (RH) of 95% maximum when tested to ASTM F2170 is required.
- Carpet tiles with WellBAC® Function backing, a Relative Humidity (RH) of 90% maximum when tested to ASTM F2170 is required.

MAINTENANCE REQUIREMENTS

- N/A

BUILDING ACT 2004 SECTION 26 COMPLIANCE

- Is the building product/building product line subject to a warning or ban under section 26 of the Building Act 2004? No