

# FORMWORK 2.0 Function Plus™



Brights / Neutrals

<b>Construction</b>	Tufted, Level Loop Pile
<b>Face Fibre</b>	Solution Dyed Nylon 6 6 (20% recycled content)
<b>Soil Release</b>	StainSmart® for soil release, liquid repellence (on light colours LRV >20)
<b>Finished Face Weight</b>	590 g/m <sup>2</sup>
<b>Gauge</b>	39.4 / 10 cm
<b>Rows</b>	52 / 10 cm
<b>Tuft Density</b>	205,000 /m <sup>2</sup>
<b>Finished Pile Height</b>	3.0 mm
<b>Standard Backing</b>	Function Plus™ Polymer modified bitumen hard back
<b>Nominal Total Thickness</b>	5.4 mm
<b>Tile Size</b>	50 cm x 50 cm
<b>Nominal Total Weight</b>	3700 g/m <sup>2</sup>
<b>Tiles per Box</b>	20 (5m <sup>2</sup> )

## PERFORMANCE

<b>Flammability (Euroclassification EN13501:1-2002)</b>	Class Bfl - s1
<b>Flammability (Radiant Panel ASTM-E-648)</b>	Class 1
<b>Flammability (Hot Metal Nut BS4790)</b>	Low Radius of Char
<b>Use Classification (EN 1307)</b>	Class 33 Heavy Commercial Use
<b>Castor Chair (BS EN 985:2001)</b>	Class A - Intensive use (r value ≥ 2.4)
<b>Static Electricity (ISO 6356)</b>	Pass ≤ 2.0 KV Permanent Conductive Fibre
<b>Impact Sound (ISO 10140-3)</b>	25 dB
<b>Sound Absorption (ISO354)</b>	0.15 (H) Class E
<b>Alpha s values</b>	125Hz 0.01, 250Hz 0.02, 500Hz 0.05, 1000Hz 0.13, 2000Hz 0.30, 4000Hz 0.36

## ENVIRONMENTAL

54% recycled content by total product weight

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

## WARRANTIES


10 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS


## INSTALLATION



## CE MARKING

--	--	--	--	--	--	--