SPECIFICATION SHEET Date: 26.02.2024 Revision 10

MAJOR FREQUENCY

Milliken

Distortion

Construction	Tufted, Textured Loop Pile
Face Fibre	Thrive® matter 90% recycled Nylon
Stain Resist	Inherently stain resistant fibre
Finished Face Weight	560 g/m ²
Gauge	47.2 / 10 cm
Rows	37.5 / 10 cm
Tuft Density	177,165 /m²
Finished Pile Height	2.9 mm
Standard Backing	WellBAC® Comfort 90% recycled open cell polyurethane cushion backing. Available with TractionBack® on request
Nominal Total Thickness	8.9 mm
Plank Size	25 cm x 100 cm
Nominal Total Weight	4100g/m ²
Planks per Box	11 (2.75m ²)

I ENI GRIVIANCE	
Flammability (Euroclassification EN13501:1-2018)	Class BfI - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A - Intensive use (r value \geq 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	31 dB ΔL_{w}
Sound Absorption (ISO354)	0.30 Class D

ENVIRONMENTAL

Alpha p values

PERFORMANCE

69% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors, 4.15 kg $\rm CO_2$ e/m² Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

125Hz 0.05, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.35

Latent Defects guarantee

CERTIFICATIONS | Company | Company



