

MIXED FORMATIONS (FLEXFORM™ LVT)

Made of Wood

Milliken LVT Flooring System

Acoustic Value	Impact Sound Pressure Level - Ln,w = 67dB
-----------------------	---

Construction	High Performance FLEXFORM™ LVT	Critical Radiant Flux (AS ISO 9239-1)	10.4 kW/m ²
Finish	ProGuard™ Reinforced Polyurethane Coating	Smoke Rate (AS ISO 9239-1)	115%.min
Wear Layer Thickness	0.55mm	Use Classification (ISO 10582)	Class 33 Heavy Duty Commercial
Tile Size:	Wood Designs: 7.25" x 48" (18.42cm x 121.92cm) Gunnison Design: 9" x 60" (228.6mm x 1524mm)	Slip Resistance Classification	P3 & R10
Overall Thickness	5mm	Heat Stability of Colour Change (ASTM F1514)	PASS
Edge Profile	Micro Bevel	Light Stability (ASTM F1515)	PASS
Recyclable	100%	Static Coefficient of Friction (ASTM D2047)	PASS
Pieces Per Box	Wood Designs: 10 pieces Gunnison Design: 5 pieces	Determination of Dimensional Stability & Curling after Exposure to Heat (ISO 23999)	≤0.25%; Curl ≤2mm
Weight Per Box	Wood Designs: 21.9kg Gunnison Design: 20.54kg	Resistance to Chemicals (ASTM F925)	PASS
Quantity Per Box	Wood Designs: 2.25m ² Gunnison Design: 2.09m ²	Residual Indentation (ISO 24343-1)	≤0.1mm
Environmental	Declare	Static Load Limit (ASTM F970)	PASS
	M/PACT™ Carbon Neutral Program	Castor Chair Resistance (ISO 4918)	PASS
	Environmental Product Declaration (EPD)	Flexibility (ISO 24344)	PASS
	GreenRate Level A by Global GreenTag	Colour Fastness to Light (ISO 105-BO2)	≥6
	Best Environmental Practice PVC		
	Works with WELL		

Recommended Installation Methods	Glue Down
Recommended Area of Use	Commercial Residential
Warranties	20-year Limited Commercial Wear Warranty



WORKS WITH WELL


Milliken’s commitment to advancing products and solutions that support human health and well-being is long-standing.






As a founding member of the **Well Living Lab** and a **Well Portfolio Member**, we aspire to design products that enhance the well-being and quality of life of indoor spaces.

We are proud to have been granted the **Works with WELL™** licence across an extensive selection of our global product portfolio, demonstrating how Milliken floor covering products align with specific strategies in the WELL Standard, the leading global standard for health and well-being.

The Works with WELL trademark licensing program recognises products and solutions that contribute to achieving specific features in the WELL Standard. Products that have earned the Works with WELL mark have been validated through one or more review cycles to give specifiers the maximum confidence in their material selections, whether working on a WELL-certified project or simply wanting to ensure they are adopting best practices for healthy, sustainable, people-first spaces for their clients.



CONCEPT		FEATURE	FEATURE NAME
	WATER	W07.2	Design Interiors for Moisture Management
	MATERIALS	X01.1	Restrict Asbestos
		X05.2	Select Compliant Architectural and Interiors Products
		X06.2	Restrict VOC Emissions from Furniture, Architectural and Interior Products
		X07.1	Select Products and Disclosed Ingredients
		X07.2	Select Products with Enhanced Ingredients Disclosure
		X08.1	Select Materials with Enhanced Chemical Restrictions
	MIND	M02.1	Provide Connection to Nature

Driven by the global demand for healthier places and healthier organisations that support people to thrive, WELL adoption has grown exponentially since its launch in 2014. WELL strategies have been used in over 5 billion square feet of space, supporting the health and well-being of an estimated 17 million people in more than 74,000 locations spanning over 130 countries.

Contact one of our team of WELL Accredited Professionals for support with your next WELL Certified project at millikenanzenquiries@milliken.com.

