

COMFORTABLE CONCRETE 2.0

Laid Bare / Urban Drama / Urban Poetry

| | |
|-------------------------|--|
| Construction | Tufted, Level Loop Pile |
| Face Fibre | Nylon 6 |
| Soil Release | StainSmart® for soil release, liquid repellence |
| Finished Face Weight | 600 g/m ² |
| Gauge | 39.4 / 10 cm |
| Rows | 39.4 / 10 cm |
| Tuft Density | 155,118 /m ² |
| Finished Pile Height | 3.3 mm |
| Standard Backing | WellBAC™ Comfort Plus® 90% Recycled Open Cell Polyurethane. Available with TractionBack® on request |
| Nominal Total Thickness | 9.9 mm |
| Nominal Total Weight | 4200 g/m ² |
| Plank Size | 50 cm x 100 cm |
| Planks per Box | 6 (3m ²) |
| Tile Size | 50 cm x 50 cm |
| Tiles per Box | 20 (5m ²) |

PERFORMANCE

| | |
|--|---|
| Flammability (Euroclassification EN13501:1-2018) | Class Cfl - s1 |
| Flammability (Radiant Panel ASTM-E-648) | Class 1 |
| Flammability (Hot Metal Nut BS4790) | Low Radius of Char |
| Use Classification (EN 1307) | Class 33 Heavy Commercial Use |
| Castor Chair (BS EN 985:2001) | Class A - Intensive use (r value ≥ 2.4) |
| Static Electricity (ISO 6356) | Pass ≤ 2.0 KV Permanent Conductive Fibre |
| Impact Sound (ISO 10140-3) | 33 dB |
| Sound Absorption (ISO354) | 0.15 Class E |
| Alpha s values | 125Hz 0.00, 250Hz 0.10, 500Hz 0.40, 1000Hz 0.25, 2000Hz 0.30, 4000Hz 0.40 |

ENVIRONMENTAL

59% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors,
8.27 kg CO₂ e/m² Embodied Carbon (EPD calculation A1-A3)
Cradle to Gate footprint 100% off set

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

www.millikenfloors.com/gb/tech

| | | | | | | | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |

INSTALLATION

CE / UKCA

| | | | | | | | | | |
|------------|------------|-------|-------------|--------------------------------------|--------------------------------------|--|--|--|--|
| | | | | | | | | | |
| Monolithic | Monolithic | Brick | Herringbone | DOP-2895-1004-01 BS EN 14041:2018 | DOP-0338-1004-01 BS EN 14041:2018 | | | | |