

PATINA VIBES (BK16 BASE)

Modular Tiles

M/PACT™

CARBON NEUTRAL PROGRAM

When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

*as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

WELLBAC®

Milliken WellBAC® open cell foam cushion provides superior durability, appearance retention and cushioning.

Up to 24% greater underfoot comfort for enhanced ergonomics whilst standing.

Up to 50% improved acoustics for quieter, more productive spaces.

Industry leading moisture management with non-reactive backings to enhance the installation process.

3rd party Verified Red-List Free products for occupant and installer well-being.

Enhanced Indoor Air Quality (Low VOC) for improved occupant and installer well-being.

| | |
|--|---|
| Standard Backing | Cushion Backing WellBAC® Comfort (PVC FREE) (Non-Reactive Cushion Backing) |
| Acoustic Value | Noise Reduction Coefficient - NRC ≥ 0.25 Impact Sound Pressure Level - Ln,w ≤47dB |
| Concrete Slab Moisture Mitigation | Site-Related Solutions (SRS). Milliken Cushion backed tile + Non-Reactive Standard adhesive means installation 60 days after a new concrete pour, fully warranted no moisture testing required. Refer millikenfloors.com.au |
| Antiviral Antibacterial | MGUARD+ Antiviral and Antibacterial Treatment. Further information refer to millikenfloors.com.au |

| | |
|------------------------------------|---|
| Construction | Tufted, Textured Loop |
| Tile Size | 50cm x 50cm |
| Yarn Type | Milliken Certified 100% Nylon |
| Stain Resist Soil Release | StainSmart® |
| Dye Method | PrintWorks™ |
| Gauge | 1/12 |
| Stitches Per Inch | 11.6 |
| Tufts | 139/in ² (2,126/100cm ²) |
| Total Tile Mass | 16 oz/yd ² (543g/m ²) |
| Recyclable | 100% |
| Nominal Total Thickness | 8.2mm |
| Nominal Pile Thickness | 2.1mm |
| Nominal Total Weight | 94 oz/yd ² (3,184 g/m ²) |

| | |
|--|---|
| Flammability (Radiant Panel Test) | CHF/CRF = 5.1kW/m ² , Smoke value = 240%.min |
| Lightfastness (AATCC 16E) | ≥ 4.0 at 80 Hours |
| Static Electricity (AATCC-134) 20% R.H., 70°F | ≤ 3.5KV |
| Indoor Air Quality CRI Green Label Plus™ | <0.5mg/m ³ (GLP3237) |
| VOC | Pass (ISO 10580:2010) |
| ACCS Grading | CEHD 4*, REHD2 6* Suitable for stairs |
| Environmental | ECS Grading - Level 4 (Certificate No. 20078) Declare - 3 rd Party Verified RED LIST FREE Cradle to Cradle - Silver Carbon Neutral Environmental Product Declaration (EPD) Health Product Declaration (HPD) |

| | | |
|---|--|------------------------------------|
| Recommended Installation Method(s) | Brick (Horizontal) | |
| Recommended Area of Use | Commercial Extra Heavy Duty | |
| Warranties | 15-year Wear Warranty | 15-year Anti-Static Warranty |
| | 15-year Dimensional Stability Warranty | 15-year Castor Chair Wear Warranty |



Alliance
Founding
Member



This WellBAC® cushion backing carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.