

SPECIFICATION SHEET DATE: 4/08/2023

## QUIET WOODS (FLEXFORM SOUND™ LVT)

Laterals | Lateral Band | Lateral Wave

Milliken LVT Flooring System



When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint\* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

°as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

Acoustic Value	Impact Sound Pressure Level - Ln,w = 61dB
----------------	---

Construction	High Performance
Construction	
	FLEXFORM SOUND™ LVT
Finish	ProGuard MAX™ Coating
Wear Layer Thickness	0.55mm
Tile Size	250mm x 1500mm
Overall Thickness	5mm
Edge Profile	Micro Bevel
Recyclable	100%
Pieces Per Box	5 pieces
Watak Dan Dan	45.241
Weight Per Box	15.24kg
Quantity Per Box	1.875m <sup>2</sup>
Environmental	Declare
	Carbon Neutral
	GreenRate by Global GreenTag
	Best Practice PVC by Global
	GreenTag
	Environmental Product
	Declaration (EPD)
L	` /

Critical Radiant Flux	6.3 kW/m <sup>2</sup>
( AS ISO 9239-1)	
Smoke Rate (AS ISO 9239-1)	313 %.min
Use Classification (ISO 10582)	Class 33 Heavy Commercial
Slip Resistance Classification	P3 & R10
Heat Stability of Colour Change	PASS
(ASTM F1514)	
Light Stability (ASTM F1515)	PASS
Static Coefficient of Friction	PASS
(ASTM D2047)	
Determination of Dimensional	≤0.25%; Curl ≤2mm
Stability & Curling after Exposure	
to Heat (ISO 23999)	
Resistance to Chemicals	PASS
(ASTM F925)	
Residual Indentation	≤0.2mm
(ISO 24343-1)	
Static Load Limit (ASTM F970)	PASS
Castor Chair Resistance	PASS
(ISO 4918)	
Flexibility (ISO 24344)	PASS
Colour Fastness to Light	≥6
(ISO 105-BO2)	

Recommended Installation Method(s)	Glue Down (Ashlar only)
Recommended Area of Use	Commercial   Residential
Warranties	22-year Limited Commercial Wear















Milliken Hybrid Flooring System is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics.

Milliken Hybrid Flooring System is 100% ortho-phthalate-free.

Milliken Hybrid Flooring System is manufactured at facilities that are ISO 9001 and ISO 14001 compliant.