

LVT Moisture XT



ADHESIVE

For LVT

2 mm, 2.5 mm & 5 mm FlexForm™ LVT



NO LIMIT



NO LIMIT



DRY TIME
10 min (wet set)



WORKING TIME
45 min



ROLL FLOOR
within 1 hr



CURE TIME
6 hrs



LIGHT TRAFFIC
3 hrs



HEAVY TRAFFIC
4 hrs



HEAVY ROLLING
LOADS : 8 hrs



2-Gallon Pail
Trowel

Resistant to Moisture From Above and Below

For use with RH up to **No RH Limit**

No pH, RH or MVER limits.

OLD ADHESIVE MUST BE REMOVED. POROSITY TEST (ASTM 3191) & BOND TEST REQUIRED. See *installation instructions* for more details.

Installation after new pour: **45 days**



The Benefits of
Milliken LVT Moisture
XT Adhesive

Milliken offers adhesive solutions for high moisture:

- Unlimited moisture protection
- No moisture or PH testing required
- No moisture vapor barrier required
- Permanent waterproof bond
- 1-step installation (no mixing)
- Limited floor prep compared to moisture mitigation systems

1/16" x 1/32" x 1/32"
U-Notch

FLOORING TYPE

2 mm, 2.5 mm & 5 mm
FlexForm™ LVT

ESTIMATED COVERAGE

165 - 220 sf/gal

WET SET INSTALL

10 minute set up time
off product install.
Installer must work
"off-the-product" to
minimize product
movement during
installation.

SCAN THE QR CODE BELOW
FOR MORE INFORMATION



LVT Moisture XT



PRODUCT CHARACTERISTICS	Product Classification	Modified urethane (isocyanate free)
	Base Chemistry	STPE polymer-based (Hybrid Propel®)
	Curing Method	Moisture cure
	Appearance	Off white
	Consistency	Smooth, low viscosity liquid
	Application	Easy troweling
	Flammability	Non-flammable
	Freeze/Thaw	Stable to 10°F (-12°C)
	Shelf Life	1 year
MOISTURE	Moisture Control	Protects flooring against unlimited moisture
	RH [ASTM F2170]	No testing required (100%)
	pH	No testing required (5-14)
	MVER [ASTM F1869]	No testing required
	Porosity [ASTM F3191]	Must be porous; all residual adhesive removed
TIME	Open Time	10 min
	Dry Time	10 min (<i>flash time</i>)
	Working Time	45 mins
	Roll & Cross Roll Floor (<i>75- 100lb roller</i>)	Between 1 - 2 hours after installation (<i>use hand roller during install</i>)
TRAFFIC	Cure Time	6 hours
	Light Traffic	3 hrs
	Heavy Traffic	4 hrs
SUSTAINABILITY	Heavy Rolling Loads	8 hrs
	Solvents	None
	Isocyanates	None
	Total VOCs	0.5 mg/m ³ or less
	Compliant with	California DPH Section 01350 Version 1.2
ACOUSTICS	Certifications	CRI Green Label Plus
	IIC	Increased IIC ratings dependent upon your ceilings and subfloor construction

STORAGE This product should be stored at temperatures between 50-90°F (15-32° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.

