

LUMENOLOGY (FLEXFORM™ LVT)

Reflective | Light Stitch | Light Wash

Milliken LVT Flooring System

When you choose M/PACT™ products, you can be sure your choice is carbon neutral. M/PACT™ carbon neutral products offset the raw materials and manufacturing carbon footprint* by using 3rd party Verified Carbon Standard Credits that support renewable energy and carbon reduction technologies to help fight climate change.

*as calculated and verified through a ISO14025/ISO14040 compliant LCA and published in third party EPD.

Construction	High Performance FLEXFORM™ LVT	Critical Radiant Flux (AS ISO 9239-1)	8.3 kW/m ²
Finish	ProGuard MAX™ Reinforced Polyurethane Coating	Smoke Rate (AS ISO 9239-1)	303%.min
Wear Layer Thickness	0.55mm	Use Classification (ISO 10582)	Class 33 Heavy Duty Commercial
Tile Size	250mm x 1000mm	Slip Resistance Classification	P3 & R10
Overall Thickness	5mm	Heat Stability of Colour Change (ASTM F1514)	PASS
Edge Profile	Micro Bevel	Light Stability (ASTM F1515)	PASS
Recyclable	100%	Static Coefficient of Friction (ASTM D2047)	PASS
Pieces Per Box	8 pieces	Determination of Dimensional Stability & Curling after Exposure to Heat (ISO 23999)	≤0.25%; Curl ≤2mm
Weight Per Box	19.5kg	Resistance to Chemicals (ASTM F925)	PASS
Quantity Per Box	2m ²	Residual Indentation (ISO 24343-1)	≤0.1mm
Environmental	Declare Carbon Neutral	Static Load Limit (ASTM F970)	PASS
	GreenRate by Global GreenTag	Castor Chair Resistance (ISO 4918)	PASS
	Best Practice PVC by Global GreenTag	Flexibility (ISO 24344)	PASS
	Environmental Product Declaration (EPD)	Colour Fastness to Light (ISO 105-B02)	≥6
Recommended Installation Method(s)	Ashlar (Vertical) Herringbone Ashlar (Random)		
Recommended Area of Use	Commercial Residential		
Warranties	22-year Limited Commercial Wear Warranty		



Milliken Hybrid Flooring System is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics.

Milliken Hybrid Flooring System is 100% ortho-phthalate-free.

Milliken Hybrid Flooring System is manufactured at facilities that are ISO 9001 and ISO 14001 compliant.