

OBEX™ GRID: CUTX

11MM CLOSED

SPECIFICATION SHEET DATE: 18 JUNE 2021

MODULAR GRID

Grid Material

100% UV-Resistant PVC

Grid Size

Nominal: 200 mm x 200 mm

Nominal Total Thickness

11 mm

Grid Color

Black

Outdoor Temperature Resistance

-30°C to 50°C

Nominal Total Weight

8,800 g/m²

Flammability (Radiant Panel Test)

CHF: 5.7 kW/ m²

Smoke Value: 656 %.min

Recommended Maintenance

Daily Vacuum, Deep Clean via Hot Water Extraction

Rolling Load

Free laid: 500 kg

Glued: 1,000 kg

Pieces Per Box

30 Pieces (1.17 m²)

TEXTILE

Textile Construction

Tufted, Cut Pile

Textile Yarn Type

Milliken-Certified WearOn® Nylon and Monofilament
Type 6 and 6,6

Dye Method

Print

Lightfastness (AATCC 16)

≥ 4.0 at 80 Hours

Crocking (AATCC 164)

≥ 4.0 Wet or Dry

Warranties

1 - Year Manufacturing Defect Warranty

5 - Year Wear Warranty



This product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.