# PREFACE

Adapt / Segment

Milliken

Construction	Tufted, Textured Loop Pile				
Face Fibre	Solution Dyed 100% Nylon				
Soil Release	StainSmart $^{\circ}$ for soil release, liquid repellence - selected colours only (on light colours LRV >20)				
Finished Face Weight	445 g/m <sup>2</sup>				
Gauge	47.2 / 10 cm				
Rows	41 / 10 cm				
Tuft Density	193 700/m <sup>2</sup>				
Finished Pile Height	2.3 mm				
Finished Pile Height Standard Backing	2.3 mm Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack® on request				
	Comfort Lite 90% recycled open cell polyurethane cushion backing				
Standard Backing	Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack <sup>®</sup> on request				
Standard Backing Nominal Total Thickness	Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack <sup>®</sup> on request 8.1 mm				
Standard Backing Nominal Total Thickness Tile Size	Comfort Lite 90% recycled open cell polyurethane cushion backing Available with TractionBack <sup>®</sup> on request 8.1 mm 50 cm x 50 cm				

#### PERFORMANCE

Flammability (Euroclassification EN13501:1-2018)	Class Bfl – s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Castor Chair (BS EN 985:2001)	Class A – Intensive use (r value $\ge$ 2.4)
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	28 dB
Sound Absorption (ISO354)	0.25 (H) Class E
Alpha s values	125Hz 0.00, 250Hz 0.05, 500Hz 0.30, 1000Hz 0.20, 2000Hz 0.25, 4000Hz 0.35

### ENVIRONMENTAL

60% recycled content by total product weight

Manufactured in ISO14001 certified location using renewable sources

M/PACT Carbon Neutral Floors, 6.07 kg  $CO_2$  e/m<sup>2</sup> Embodied Carbon (EPD calculation A1-A3) Cradle to Gate footprint 100% off set

## WARRANTIES

12 year wear warranty Lifetime Antistatic guarantee Latent Defects guarantee

\*StainSmart® Applied to the following colours only

Granite, Mist



#### INSTALLATION



CE / UK	(CA					
DOP-2895-1004-02 BS EN 14041:2018	UK DOP-0338-1004-02 BS EN 14041:2018	B <sub>fl</sub> -s1	<sup>°</sup> Е1 нсно	° ZZ	DS-	

Design Copyright – Milliken & Company. This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.