



Registration Certificate

Carpet Name: BK9 CUSTOM DESIGNS

Licensee: MILLIKEN (AUSTRALIA) PTY LTD
Licence Number: 008
Label Number: 16098

ACCS Contract Grading: CEHD 4*
ACCS Residential Grading: NONE
Suitable for Stairs: Yes

Date Printed: 20/06/2016



Allan Firth



Allan Firth
Secretary ACCS



Administered by the Carpet Institute of Australia Limited ABN 11 006 829 303
PO Box 7172, St Kilda Road, Melbourne Victoria 3004 Tel: (03) 9804 5559 • Fax: (03) 9804 5560
Email: info@carpetoz.com.au • www.carpetinstitute.com.au

This certificate remains the property of the Carpet Institute of Australia Limited.

Carpet Details:

Company: MILLIKEN (AUSTRALIA) PTY LTD
Licence No: 008

Label No: 16098
Office No: 6372

Names:

BK9 CUSTOM DESIGNS

Details:

Awarded Res Grade: NONE
 Awarded Con Grade: CEHD 4*
 Registered On: 20/06/2016
 Active: Yes
 Date In-Active:
 Manufacture Method: Tufted
 Twist Set: N/A
 Dyeing Method: Yarn Dyed
 #Colours/Designs: 12
 Backing Type: Foam
 Felted: N/A
 Spinning System: BCF
 Insect Resist Agent: N/A
 Filament: /
 Master Product: 14205

Test Results:

Pile Mass g/m² (oz/yd²): 509 (15.0)
 SPM g/m² (oz/yd²): 310 (9.1)
 Stated Pile Height (mm): 2.0
 Minimum Pile Height (mm): 0.0
 Maximum Pile Height (mm): 0.0
 Dynamic Loading Loss (%): 20.6
 Static Loading Loss (%): 8.8
 Tex (g/1000m): 250
 Measured Pile Thickness (mm): 2.4
 Machine Gauge (Tufts/dm): 47.0
 Meas Tufts Perp to Selvedge: 48.1
 Meas Tufts Para to Selvedge: 38.9
 Treated For Soiling Resistance: Yes
 Soil Resist Inhibitor: Yes
 Stain Resist Inhibitor: Yes

Hexapod Scores:

Texture		Colour		Thickness	
WA		WA		(mm)	(%)
1500: 4.0	3.5	4.0	4.0	0.4	16.7
8000: 3.0	2.5	3.5	3.0	0.6	25.0

Quality Assurance Test:

Cut Pile (%): 0
 Loop Pile (%): 100
 Panel Assessment Contract: 15
 Panel Assessment Residential: 15
 Suitable For Stairs: Yes
 Tile: Yes SheetGoods: No
 Fibre Signature: NBA:100

ACCS Test:

	Con	Res	Max
SPM/PH Ratio:	11.9	16	16
Volume Density:	12.2	12.2	20
Tuft Density:	9	9	9
Dyn Load:	4	4	5
Stat Load:	5	5	5
Soiling Prop:	14	14	16
Abrasion Res:	7.9	7.9	10
Sub Total:	64	68.1	81
Panel Assess:	15	15	19
Total:	79	83.1	100
Calc Residential Grade:	REHD2	6*	
Calc Contract Grade:	CHD	3*	

Calculations

Pile Height(mm): 3.4
 Tuft Density(per dm²): 1871.1
 GSPM(g/m²): 397.0
 GSPM (abrasive) (g/m²): 275.0
 Soiling Propensity: 12.0 +2.0

OAF Values

OAF: 4.2
 Calc Density (+-5%): 0.12 0.129 0.14
 Base Fibre: NYLON
 Benchmarks:
 RHD1 0 RHD2 3.5
 REHD1 3.5 REHD2 3.5

Environmental Classification:

ECS:

Level: 0

	Calc	B/M	P/F
Acoustic:	2.4	3	
Thermal:	18.6	15	PASS
VOC:			
TVOC	0		

Notes:

20/06/2016 - Cloned From Master - (14205) by S Murphy.