

Non-Reactive Standard



ADHESIVE

For Carpet

Non-reactive adhesive for most applications.
(Exception: Extreme Moisture)



NO LIMIT



NO LIMIT
Renovations



NO LIMIT
New Construction



DRY TIME
10-20 Min



WORKING TIME
Indefinite
When Clean



CURE TIME
10-20 Min



LIGHT TRAFFIC
Immediate



HEAVY TRAFFIC
Immediate



HEAVY ROLLING
LOADS: Immediate
with protection



4-Gallon Pail
Trowel / Roll-on

Non-Reactive Pressure Sensitive Adhesive

NEW CONSTRUCTION OR RENOVATION:

For use with RH up to: **No Limit**

Installation after new pour: **45 days**

No testing required. No pH/RH limit.



The Benefits of
Milliken Adhesives

Milliken offers adhesive solutions for any scenario:

- Modular carpet, LVT, mixed-media
- Normal RH and pH
- Extreme RH and no-testing solutions
- Trowel-on and Spray options for most applications
- No primers, no sealants, limited floor prep required



1/16" x 1/32" x 1/32"
U-Notch

FLOORING TYPE

Modular Carpet Tile

ESTIMATED COVERAGE
180 - 225 sf/gal



3/4" - 1"
Nap Paint Roller

FLOORING TYPE

Modular Carpet Tile

ESTIMATED COVERAGE
Up to 350 sf/gal

SCAN THE QR CODE BELOW
FOR MORE INFORMATION



Non-Reactive Standard Adhesive

PRODUCT CHARACTERISTICS	Product Classification	Roll or Trowel Pressure Sensitive Adhesive
	Base Chemistry	Acrylic Emulsion
	Appearance	Mint Green to Green Tint as adhesive dries
	Consistency	Thin Syrup
	Application	Trowel or Roller
	Flammability	Non-flammable
	Freeze/Thaw	Protect From Freezing
	Shelf Life	2 Years (Unopened)
MOISTURE	RH	Renovation or New Construction: No limit, no testing if installed 45 days after a new pour.
	pH	No limit, no testing
	Bond Test	Must perform bond test
TIME/TRAFFIC	Open Time	Indefinite when clean
	Dry Time	10-20 Min
	Working Time	Indefinite when clean
	Traffic	Immediately
SUSTAINABILITY	Solvents	None
	Compliant with Certifications	CRI Green Label Plus

STORAGE This product should be stored at temperatures between 40-100°F (4-38° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

CAUTION DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY For Milliken installation instructions and warranties, visit millikenfloors.com.